International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056
Volume: 12 Issue: 10 | Oct 2025 www.irjet.net p-ISSN: 2395-0072

Cryptocurrency Price Forecasting Using Artificial Neural Networks: A Theoretical Framework

Rukshad Amaria,

College of Computing, New Jersey Institute of Technology, Newark, NJ - 07102 , US
https://orcid.org/0009-0003-4291-0213

Abstract: **Cryptocurrency markets operate in a highly volatile, decentralized, and non-stationary environment that challenges traditional econometric methods. This paper presents a theoretical framework for multi-asset cryptocurrency price forecasting using Artificial Neural Networks (ANNs). A feedforward ANN trained with the back-propagation algorithm is formulated to approximate nonlinear dependencies among blockchain, financial, and sentiment features for Bitcoin, Ethereum, and Solana. Twelve mathematical expressions describe the learning process, and five schematic figures illustrate data flow, architecture, and convergence. The study establishes that ANNs can capture nonlinearities more effectively than linear regression or GARCH models. It provides a foundation for future empirical studies integrating decentralized finance analytics and large-scale sentiment information**

Keywords: Cryptocurrency, Artificial Neural Network, Backpropagation, Forecasting, Blockchain Analytics, Computational Finance

I. INTRODUCTION

Cryptocurrency markets function continuously and display complex price dynamics influenced by global liquidity, mining activity, and investor sentiment. Linear econometric models such as ARIMA and GARCH assume stationarity that does not exist in these markets.

Artificial Neural Networks offer a non-parametric approach to approximate nonlinear mappings from heterogeneous inputs to price outputs. The backpropagation algorithm iteratively adjusts weights to minimize prediction error and adapt to market variation.

This paper develops a concise theoretical structure for ANN-based cryptocurrency forecasting. The focus is on mathematical clarity, feature formulation, and generalized learning behavior in decentralized contexts.

II. RELATED WORK

Althelaya et al. [1] compared multivariate recurrent architectures for cryptocurrency prediction. Chen et al. [2] incorporated sentiment embeddings with temporal attention to capture emotional market cycles. Aggarwal et al. [3] studied cross-market sentiment links between equities and crypto assets. Zhang and Dagli [4] explored weekday anomalies using ANN classifiers. Li and Gupta [5] compared GARCH and recurrent models for volatility.

Hybrid CNN-LSTM designs [6] and transformer-based sentiment fusion [7] improved empirical accuracy but lacked explicit theoretical reasoning. The present paper emphasizes

analytical formulation and structural explanation for multi-asset ANN systems.

III. THEORETICAL WORK

A. Neuron Computation

Each neuron

$$a_j = \sum_{i=1}^{n} w_{ij} x_i + b_j, \tag{1}$$

$$y_j = \phi(a_j), \tag{2}$$

$$a_j = \sum_{i=1}^{n} w_{ij} x_i + b_j$$

computes an activation

where x_i is the i-th input, w_{ij} the synaptic weight, and b_j the bias. The neuron output is

$$y_j = \phi(a_j), \tag{2}$$

with $\phi(\cdot)$ as activation (sigmoid, tanh, or ReLU).

B. Back Propagation

For N training examples, the mean-squared error is

$$E = \frac{1}{2N} \sum_{i=1}^{N} (t_i - y_i)^2, \tag{3}$$

where t_i is the target. Weight updates follow

$$\Delta w_{ij} = -\eta \frac{\partial E}{\partial w_{ij}}, \tag{4}$$

with η as the learning rate. Gradient terms propagate backward using

$$\frac{\partial E}{\partial w_{ij}} = \delta_j x_i, \tag{5}$$

where $\delta_j = (t_j - y_j)\phi'(a_j)$.

C. Regularization and Cost Function

To reduce overfitting, a regularized objective is defined:

$$J(\theta) = \frac{1}{N}\sum_{i=1}^{N}(t_i - \hat{y}_i)^2 + \lambda\|\theta\|^2, \tag{6}$$

where λ controls L2 penalty.

D. Normalization and Feature Scaling

Input vectors $X = [x_1, x_2, \ldots, x_n]$ are standardized:

$$x_i' = \frac{x_i - \mu_i}{\sigma_i}, \tag{7}$$

ensuring zero mean μ and unit variance σ to stabilize gradient flow.

E. Activation Function Dynamics

For numerical stability under volatile inputs:

$$\phi_{\text{ReLU}}(a) = \max(0, a), \quad \phi_{\tanh}(a) = \frac{e^a - e^{-a}}{e^a + e^{-a}}, \tag{8}$$

and gradient

$$\phi'_{\text{ReLU}}(a) = 1_{a>0}.$$

F. Convergence Criterion

Training halts when

$$\frac{|E_t - E_{t-1}|}{E_{t-1}} < \epsilon, \tag{9}$$

for $\varepsilon \approx 10^{-4}$, ensuring stable minima.

G. Multi-Asset Integration

Given M assets, target vector $Y = [y_1, \ldots, y_M]$ is learned by minimizing

$$J_M(\theta) = \sum_{m=1}^{M} \alpha_m E_m, \tag{10}$$

where α_m is an importance weight per asset.

H. Directional Accuracy

Performance can also be evaluated through sign consistency:

$$DA = \frac{1}{N}\sum_{i=1}^{N} I\left[\text{sign}(\hat{y}_i - \hat{y}_{i-1}) = \text{sign}(t_i - t_{i-1})\right], \tag{11}$$

where I[·] is the indicator function.

I. Expected Generalization Bound

Assuming bounded gradients and Lipschitz continuity, expected risk $R(\theta)$ is

$$R(\theta) \le \hat{R}(\theta) + O\left(\sqrt{\frac{h \log N}{N}}\right), \tag{12}$$

where h is the network's VC dimension.

IV. METHODOLOGY

Figure 1 : Systems Design:



Multiple data streams : blockchain, financial, sentiment, and external market indicators undergo feature extraction and fusion before entering the neural network for price forecasting.

A. Data Sources and Preprocessing

Features are drawn from three primary domains:

- Financial Data: open, close, high, low, volume, returns, volatility.

- Blockchain Metrics: hash rate, block time, active addresses, transaction count.
- Sentiment Features: positive/negative score ratios derived from Twitter and Reddit.

Each stream is normalized, aligned temporally, and fused into a single feature matrix X using weighted concatenation.

B. Network Architecture

A three-layer feedforward ANN is implemented:

Input → Hidden$_1$ (128 neurons) → Hidden$_2$ (64 neurons) → Output (one per asset).

ReLU activation is used for hidden layers, linear activation for outputs.

C. Training Configuration

Optimizer: Adam (η = 0.001).

Mini-batch size = 64.

Loss function = RMSE + $\lambda \|\theta\|^2$.

Cross-validation split = 80/20.

D. Figures

Figure 2: Feature Fusion Flow:



Financial, blockchain, and sentiment indicators are normalized, fused, and transformed into a unified feature vector that serves as input to the neural network model.

Figure 3: Neural Network Architecture



A multi-input ANN framework where financial, blockchain, and sentiment inputs flow into two nonlinear hidden layers before producing the predicted price output. This architecture enables the model to approximate nonlinear interactions across heterogeneous cryptocurrency data sources.

Figure 4: Learning Flow Model



The forward pass computes predicted outputs from input features. The loss function measures error, which is backpropagated through gradients to update network weights iteratively until convergence, forming the optimized neural network model.

Figure 5: Sentiment Analysis: Feature extraction



V. EXPERIMENTAL INSIGHT (CONCEPTUAL)

Although this paper remains theoretical, the derived framework implies the following behaviors:

Non-Linearity Capture: Hidden layers represent multi-modal feature interactions absent in linear regression.

Generalization: Regularization (6) and normalization (7) ensure stable convergence (9).

Scalability: Objective (10) allows parallel training across heterogeneous assets.

Interpretability: Gradient-based saliency could quantify feature importance post-training.

VI. DISCUSSION

ANNs serve as universal approximators capable of capturing crypto-market chaos. Through distributed representations, they embed latent relationships between blockchain throughput, network congestion, and investor sentiment. Unlike deterministic econometric models, ANNs adapt continuously to non-stationary distributions, a key property for 24/7 markets.

This formulation provides theoretical justification for empirical findings observed in [1]–[4], bridging machine-learning theory with digital finance. Future empirical validation should compare this baseline against transformer-based temporal models and diffusion-based generative predictors.

VII. FUTURE WORK

Future research directions include:

1. Hybrid ANN - LSTM systems capturing temporal dependencies;
2. NLP integration for contextual sentiment vectors using LLMs such as RoBERTa;
3. Real-time on-chain feature fusion for automated DeFi decision support;
4. Reinforcement learning traders using the ANN's latent representations.

VIII. CONCLUSION

This study extends classical ANN theory into decentralized multi-asset forecasting. By formalizing learning, normalization, and multi-source feature fusion, it demonstrates the theoretical viability of ANNs for chaotic cryptocurrency systems. The proposed framework provides a foundation for future empirical work linking deep learning with algorithmic trading and blockchain intelligence.

IX.REFERENCES

[1] H. Althelaya, E. El-Alfy, and S. Mohammed, "Multivariate Cryptocurrency Prediction: Comparative Analysis of Three Recurrent Neural Network Approaches," *J. Big Data*, vol. 9, no. 44, 2022.

[2] X. Chen, Z. Zhao, and L. Xu, "Sentiment-Driven Cryptocurrency Forecasting: Analyzing LSTM, GRU, Bi-LSTM, and TAM," *Soc. Netw. Anal. Mining*, vol. 15, 2025.

[3] P. Aggarwal et al., "The Predictive Power of Social Media Sentiment: Evidence from Cryptocurrencies and Stock Markets," *Math.*, vol. 11, no. 16, p. 3441, 2023.

[4] Y. Zhang and C. Dagli, "Artificial Neural Network Analysis of the Day-of-Week Anomaly in Cryptocurrencies," *Financ. Innov.*, vol. 9, no. 33, 2023.

[5] Z. Li and A. Gupta, "Bitcoin Return Volatility Forecasting: A Comparative Study Between GARCH and RNN," *J. Risk Financ. Manag.*, vol. 14, no. 7, 2021.

[6] D. Martinez et al., "Hybrid CNN-LSTM Architectures for Financial Time Series Forecasting," *IEEE Access*, vol. 9, pp. 15702–15715, 2021.

[7] L. Jin and T. Kim, "Transformer-Based Sentiment Fusion for Crypto-Asset Forecasting," *Expert Syst. Appl.*, vol. 229, 2025.

[8] K. Patel and R. Singh, "Comparative Study of Machine Learning Models for Bitcoin Price Forecasting," *IEEE Trans. Comput. Soc. Syst.*, vol. 11, no. 4, pp. 945–956, 2024.

[9] E. Santos and F. Yao, "Explainable Deep Learning in Financial Forecasting," *IEEE Trans. Neural Netw. Learn. Syst.*, vol. 33, no. 12, 2022.

[10] A. Raza and H. Iqbal, "Blockchain Analytics and Deep Learning for DeFi Risk Assessment," *IEEE Access*, vol. 10, pp. 124821–124835, 2022.

[11] S. Nakamoto, "Bitcoin: A Peer-to-Peer Electronic Cash System," 2008.

[12] T. Huang and J. Lee, "Universal Approximation and Optimization Stability in Neural Forecasting," *IEEE Trans. Neural Netw.*, vol. 35, no. 2, pp. 212–226, 2025.