International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056
Volume: 13 Issue: 01 | Jan 2026 www.irjet.net p-ISSN: 2395-0072

DEEP LEARNING APPROACHES FOR EARLY-STAGE BRAIN STROKE RECOGNITION

Nikhil N Y[1], Kumarswamy S[2]

[1] *Students , M.Tech IoT, Dept. of Computer Science, University of Visvesvaraya College of Engineering, Bengaluru, India*

[2] *Dr. Kumarswamy S, Professor, Dept. of Computer Science, University of Visvesvaraya College of Engineering, Bengaluru, India*

Abstract - *Stroke is a severe neurological condition and remains a major contributor to mortality and prolonged disability across the globe, making timely and precise diagnosis essential to prevent permanent brain injury. With recent progress in artificial intelligence, automated diagnostic systems have emerged as valuable tools to support clinicians in early stroke identification and clinical decision-making. This research introduces a deep learning–driven method for detecting brain stroke using medical imaging modalities, specifically computed tomography (CT) and magnetic resonance imaging (MRI) scans. The proposed framework utilizes a convolutional neural network (CNN) enhanced through transfer learning based on the ResNet50 architecture to automatically learn and extract meaningful features from brain images. To improve data quality and model reliability, preprocessing steps including image normalization, noise filtering, and resizing are performed prior to training. The developed model is designed to distinguish between stroke-affected and healthy brain images, achieving dependable classification results with strong predictive performance. Model effectiveness is assessed using standard evaluation measures such as accuracy, precision, recall, and F1-score. Experimental findings indicate that deep learning–based approaches offer substantial improvements in both detection accuracy and processing efficiency when compared to conventional diagnostic techniques. The proposed system demonstrates strong potential as a clinical decision support solution, facilitating early diagnosis and prompt medical intervention, which can ultimately enhance patient recovery rates and reduce stroke-related death and disability.*

***Key Words*: Stroke identification, machine learning, neuroimaging, brain-computer interface, early detection, personalized rehabilitation, predictive algorithms.**

1. INTRODUCTION

Stroke is a critical neurological disorder that arises from an interruption in cerebral blood flow, leading to injury of brain tissue and impairment of vital neurological functions. It remains a leading cause of death and persistent disability worldwide. Because neuronal damage progresses rapidly during a stroke episode, prompt detection and immediate medical treatment are essential to improve patient survival and minimize long-term functional deficits. Medical imaging modalities such as Computed Tomography (CT) and Magnetic Resonance Imaging (MRI) are widely used for stroke assessment and diagnosis. Despite their effectiveness, the manual analysis of these scans can be labor-intensive and relies heavily on the skill and experience of clinicians. In high-pressure emergency settings, diagnostic delays or subjective interpretation may negatively influence clinical outcomes. As a result, there is an increasing demand for intelligent and automated diagnostic solutions that can support healthcare professionals by enabling quicker, more consistent, and more accurate stroke detection.



Fig -1: Data Flow Diagram (Level-1) for Stroke Detection and Prediction

Recent progress in artificial intelligence, especially in the fields of machine learning and deep learning, has demonstrated significant promise for medical image interpretation. Among these techniques, Convolutional Neural Networks (CNNs) have shown exceptional capability in learning intricate visual features and recognizing subtle patterns within images that may be difficult for human observers to detect.

By utilizing these strengths, deep learning models can substantially improve both the precision and efficiency of stroke identification from neuroimaging data. This work is centered on designing an automated system for brain stroke detection by applying deep learning methods to medical imaging datasets. A CNN-based framework built on the

ResNet50 architecture is used to examine CT and MRI scans and categorizes them into stroke-positive and normal classes.

To enhance data quality and maintain uniformity across images, several preprocessing operations are performed prior to model training. The proposed solution is intended to assist medical practitioners by serving as a dependable clinical decision support tool that facilitates early stroke detection, minimizes diagnostic delays, and contributes to improved patient treatment and outcomes.

1.1 Motivation

Stroke remains a critical public health issue worldwide, accounting for a substantial proportion of deaths and long-term neurological disabilities. Due to its sudden occurrence and rapid deterioration of brain function, timely identification of stroke is vital for effective medical intervention and patient recovery. Even minimal delays in diagnosis can result in permanent neurological impairment, highlighting the necessity for faster and more dependable diagnostic solutions.

While imaging modalities such as Computed Tomography (CT) and Magnetic Resonance Imaging (MRI) are standard tools for stroke evaluation, their analysis largely relies on the skill and availability of trained radiologists. In emergency clinical environments, dependence on manual interpretation can introduce diagnostic delays and variability, potentially affecting treatment outcomes. Moreover, the increasing burden on healthcare systems has intensified the need for automated diagnostic aids capable of delivering prompt and accurate assessments.

Advances in artificial intelligence, particularly in deep learning, have opened new avenues for improving medical image analysis. Convolutional Neural Networks (CNNs) have shown remarkable effectiveness in extracting high-level features from large volumes of imaging data and detecting subtle pathological patterns that may escape conventional diagnostic methods. In response to these clinical challenges and technological developments, this project focuses on designing an intelligent deep learning–based framework for brain stroke detection.

The proposed approach employs the ResNet50 architecture in combination with robust image preprocessing techniques to enhance diagnostic precision and computational efficiency. By reducing diagnostic time and assisting clinicians with reliable decision support, the system aims to facilitate early intervention and improve overall stroke management. Ultimately, this work seeks to contribute to better patient outcomes and more efficient clinical workflows in stroke care.

1.2 Scope

The scope of this project involves the development and implementation of an intelligent brain stroke detection framework based on deep learning and medical image analysis. The proposed system is designed to examine brain CT and MRI scans to accurately and promptly determine the presence of stroke. By employing advanced convolutional neural network architectures, specifically the ResNet50 model, the system automates both feature learning and image classification, thereby minimizing dependence on manual image interpretation. The project also encompasses the use of comprehensive image preprocessing methods, including noise filtering, normalization, image resizing, and data augmentation, to enhance image clarity and maintain uniformity across varied datasets. These preprocessing strategies improve the model's robustness and enable reliable performance when handling diverse medical imaging data.

The developed system categorizes input images into stroke-positive and non-stroke classes, delivering informative diagnostic results to support healthcare professionals in clinical decision-making. Furthermore, the project includes a thorough evaluation of model performance using established metrics such as accuracy, precision, recall, and F1-score to ensure reliability and clinical applicability. Although the system is intended to function as a supportive diagnostic tool rather than a substitute for medical expertise, it holds potential for future integration into clinical environments or telemedicine applications. Overall, this work aims to enhance early stroke detection, increase diagnostic efficiency, and improve patient outcomes through the effective application of deep learning technologies in healthcare.

1.3 Problem Statement

Stroke is a critical neurological disorder that demands prompt and precise diagnosis to minimize brain injury and long-term functional impairment. Although CT and MRI imaging techniques are commonly employed for stroke evaluation, their interpretation relies heavily on the expertise of trained medical professionals. In emergency scenarios, the limited availability of specialists can lead to delays in diagnosis, while manual examination of images is often time-intensive and may result in variability in clinical assessments.

The increasing incidence of stroke cases has intensified the need for efficient and dependable diagnostic solutions. Many existing automated techniques still struggle with limited accuracy and lack robustness when applied to diverse imaging data. Conventional machine learning methods depend on manually designed features, which are often insufficient for capturing the complex patterns present in medical images. Consequently, there is a growing requirement for intelligent systems capable of automatically analyzing neuroimaging data. Deep learning–based approaches offer a promising solution by enabling rapid and reliable stroke detection, thereby supporting early diagnosis and informed clinical decision-making.

2. RELATED WORKS

Research in stroke detection and prediction has advanced considerably alongside developments in machine learning techniques and medical imaging technologies. Early investigations in this area largely relied on conventional machine learning algorithms applied to structured clinical datasets. Methods such as Logistic Regression, Decision Trees, Support Vector Machines (SVM), and Random Forests were frequently employed to estimate stroke risk using patient-related factors including age, blood pressure, glucose levels, and medical history. While these approaches contributed valuable predictive insights, their performance was constrained by dependence on manually engineered features and limited capability to model the complex spatial characteristics inherent in medical images.

As neuroimaging data became more accessible, researchers began exploring image-based stroke detection methods. Initial approaches utilized handcrafted image features such as texture analysis, edge-based descriptors, and statistical measurements derived from CT and MRI scans. These features were subsequently classified using traditional machine learning classifiers. Although image-based methods demonstrated improved diagnostic potential compared to systems based solely on clinical data, their effectiveness was strongly influenced by feature selection quality and required substantial domain expertise.

The introduction of deep learning, particularly Convolutional Neural Networks (CNNs), represented a significant shift in medical image analysis. CNN-based models enabled automatic learning of hierarchical representations directly from raw imaging data, removing the need for manual feature extraction. Numerous studies reported enhanced accuracy in identifying ischemic and hemorrhagic strokes using CNN architectures trained on CT and MRI images. These models proved capable of detecting subtle pathological patterns that are often challenging for human observers to recognize.

Transfer learning further accelerated progress in stroke detection research by mitigating challenges associated with limited labeled medical datasets. Pre-trained deep learning architectures such as Alex Net, VGG16, VGG19, and Res Net were fine-tuned for stroke classification tasks. Among these models, Res Net-based architectures attracted considerable attention due to their use of residual connections, which allow deeper networks to be trained effectively without vanishing gradient issues. Research employing Res Net models consistently demonstrated improved accuracy, sensitivity, and robustness compared to shallower CNN designs.

Despite notable advancements, several limitations persist in current stroke detection systems. Challenges including class imbalance, restricted dataset diversity, limited model interpretability, and constraints on real-time clinical deployment continue to impact reliability and adoption in healthcare environments. These issues underscore the need for efficient deep learning frameworks that deliver accurate, interpretable, and rapid stroke detection. Building upon prior research, the proposed system employs a ResNet50-based CNN model along with effective image preprocessing strategies to enhance diagnostic accuracy and provide meaningful support for clinical decision-making.



Fig -2: Image Preprocessing Flow for RGB to Gray scale Conversion

3. IMPLEMENTATION AND WORKING

3.1 System Overview

The brain stroke prediction system is developed as an intelligent clinical support solution that applies deep learning methods to the analysis of medical brain imaging data. Its main goal is to aid healthcare practitioners by automatically detecting abnormalities associated with stroke in CT or MRI scans. The system emphasizes high diagnostic accuracy, consistent performance, and rapid analysis, all of which are essential for effective stroke assessment and early intervention.

3.2 Data Acquisition

Medical imaging data serves as the core input for the proposed system. Brain CT and MRI scans are obtained from trusted datasets and clinical repositories. Each image is annotated as either stroke-positive or stroke-negative to support supervised learning. Careful data acquisition and labeling ensure that the model is exposed to representative imaging patterns associated with various stroke conditions, thereby improving learning effectiveness and classification performance.

3.3 Image processing

Image preprocessing is a crucial stage that prepares raw medical scans for effective analysis. To ensure uniformity across the dataset, images are resized to a standardized resolution and normalized. Various noise reduction techniques are applied to improve visual clarity, and conversion to gray scale is performed to decrease computational overhead while preserving important diagnostic features.

3.4 Image Enhancement and Segmentation

To enhance the visibility of stroke-impacted areas, image enhancement methods such as contrast optimization and sharpening are employed. Segmentation techniques are then used to extract regions of interest within the brain by distinguishing abnormal tissue from healthy structures. This process enables the model to concentrate on clinically significant areas, thereby improving the effectiveness of subsequent analysis.

3.5 Feature learning using Deep Learning

Rather than depending on manually engineered features, the system employs deep learning techniques to automatically extract meaningful representations from brain images. The convolutional neural network learns distinctive patterns, including texture characteristics, structural shapes, and intensity differences, that are typically associated with stroke-affected areas. This automated feature learning approach enhances classification accuracy while minimizing human bias and subjectivity.



Fig -3: Functional Use Case Diagram for Stroke Prediction System

3.6 ResNet50 Architecture

The proposed system utilizes the ResNet50 architecture, a deep convolutional neural network designed with residual learning mechanisms. These residual connections allow the network to effectively model complex patterns by overcoming issues related to vanishing gradients during training. Owing to its deep structure and strong feature extraction capability, ResNet50 is particularly well-suited for analyzing medical images and capturing high-level representations relevant to stroke detection.

3.7 Model Training and Validation

During the training phase, the model learns to distinguish between stroke-affected and normal images by iteratively updating its network parameters in response to prediction errors. The dataset is partitioned into training and validation subsets to track learning performance and reduce the risk of over fitting. Validation plays a crucial role in assessing the model's ability to generalize effectively to previously unseen data.

3.8 Stroke Classification Process

After training, the model is capable of categorizing new brain images as either stroke-positive or stroke-negative. The prediction is expressed as a probability value that reflects the estimated likelihood of stroke occurrence. Providing results in probabilistic form enables clinicians to evaluate risk levels more effectively, rather than depending only on a strict binary outcome.

3.9 Result Interpretation and Output

The final outputs are displayed in a clear and user-friendly manner. The system indicates whether a stroke has been identified and includes confidence scores associated with each prediction. By presenting results in this way, the system assists medical practitioners in making quicker and more informed clinical decisions.

3.10 System Effectiveness and Reliability

The system's effectiveness is evaluated using standard performance indicators such as accuracy, sensitivity, and specificity. Reliability is strengthened through the use of thorough image preprocessing methods, advanced deep feature learning, and well-structured validation strategies. The proposed solution is intended to serve as an assistive diagnostic tool that complements clinical expertise, rather than replacing the decision-making role of medical professionals.

4. FUTURE SCOPE

Future enhancements to the brain stroke prediction system can focus on improving accuracy, flexibility, and real-world clinical applicability. Expanding the training dataset to include a larger and more diverse collection of brain images from multiple medical institutions and varied patient populations would improve the model's generalization across different imaging conditions and demographics. Additionally, extending the model to classify different types

of stroke, such as ischemic and hemorrhagic strokes, could provide more precise and clinically actionable results.
Another promising direction involves integrating non-imaging data, including patient medical history, lifestyle factors, and physiological parameters, alongside imaging inputs. This multimodal approach could enable a more holistic assessment of stroke risk and severity. Enhancing computational efficiency to achieve faster inference times would further improve suitability for emergency and time-sensitive clinical environments.

Exploration of advanced deep learning architectures with improved learning efficiency may help increase detection accuracy while reducing computational overhead. Incorporating explainable AI techniques to clarify how predictions are generated can enhance trust and acceptance among healthcare professionals. Deployment through cloud-based or web-enabled platforms would facilitate remote access and support telemedicine use cases. Continuous learning from new data and extensive clinical validation will be essential to ensure the system's long-term reliability, safety, and readiness for integration into real-world healthcare settings.

5. CONCLUSION

This project demonstrates the effectiveness of deep learning methods in supporting early brain stroke detection through medical image analysis. By employing a convolutional neural network–based framework, the system successfully learns discriminative features from CT and MRI brain scans and accurately differentiates between stroke-affected and normal cases. The combination of image preprocessing, automated feature extraction, and robust classification contributes to enhanced diagnostic consistency and reliability.

The findings highlight the potential of advanced neural network architectures to improve clinical decision support by reducing reliance on manual image interpretation and minimizing diagnostic delays. While the system is not intended to replace medical professionals, it serves as a valuable assistive tool that supports clinicians in making timely and well-informed decisions. Overall, the proposed approach shows strong promise in improving stroke diagnosis and provides a solid foundation for future advancements in intelligent, AI-driven healthcare systems.

6. ACKNOWLEDGEMENT

We extend our sincere gratitude to Professor Subhasish Tripathy (Principal), Dr. Thriveni J (HOD – CSE Department), Dr. Kumarswamy S (Professor and Project Guide), Teaching and Non- Teaching staffs of University of Visvesvaraya College of Engineering, Bengaluru- 560001.

7. REFERENCES

[1] J. Chaki and M. Woźniak, "Deep learning and artificial intelligence in brain stroke detection, diagnosis, and post-stroke rehabilitation management," IEEE Access, vol. 12, pp. 45 210–45 236, 2024.

[2] R. Zhang, C. Wang, S. He, C. Zhao, and K. Zhang, "An adaptive brain–computer interface to enhance motor recovery after stroke," IEEE Trans. Neural Syst. Rehabil. Eng., vol. 31, pp. 1845–1856, 2023.

[3] S. S. Mousavi and M. S. Majedi, "Microwave imaging-based brain stroke classification using generalized Tikhonov regularization," IEEE J. Electromagn., RF Microw. Med. Biol., vol. 7, no. 3, pp. 198–206, 2023.

[4] K. Wu, "Dynamic reconfiguration of brain functional networks in stroke using deep learning," IEEE Trans. Med. Imaging, vol. 43, no. 2, pp. 612–623, 2024.

[5] J. Su, J. Wang, and W. Wang, "An adaptive hybrid brain–computer interface for hand function rehabilitation of stroke patients," IEEE Trans. Biomed. Eng., vol. 71, no. 1, pp. 110–121, 2024.

[6] O. Karadima, P. Kosmas, P. Lu, and I. Sotiriou, "Experimental validation of DBIM-TwIST for brain stroke detection using anatomical head phantoms," IEEE Trans. Antennas Propag., vol. 71, no. 5, pp. 4120–4132, 2023.

[7] T. Janyalikit and C. A. Ratanamahatana, "Time-series shapelet-based movement intention detection for asynchronous BCI stroke rehabilitation," IEEE Access, vol. 10, pp. 98 455–98 468, 2023.

[8] M. M. Yüksel, G. Courtine, and S. Sun, "Low-intensity focused ultrasound neuromodulation for stroke recovery," IEEE Rev. Biomed. Eng., vol. 17, pp. 1–14, 2024.

[9] A. R. Khan et al., "Deep learning-based ischemic stroke detection using CT images," IEEE Access, vol. 11, pp. 120 331–120 343, 2023.

[10] H. Liu, Y. Chen, and Z. Wang, "Automated stroke lesion segmentation using convolutional neural networks," IEEE Trans. Med. Imaging, vol. 42, no. 7, pp. 2045–2056, 2023.

[11] S. Patel and R. Mehta, "Transfer learning approaches for stroke detection in brain MRI," IEEE Intell. Syst., vol. 39, no. 1, pp. 58–67, 2024.

[12] M. Alsharif et al., "Explainable AI for clinical stroke diagnosis using deep neural networks," IEEE Access, vol. 12, pp. 15 410–15 423, 2024.

[13] Y. Park and J. Lee, "Vision transformer-based stroke classification in medical imaging," IEEE Trans. Artif. Intell., vol. 5, no. 2, pp. 321–332, 2024.

[14] L. Chen, Q. Zhou, and M. Sun, "Multi-modal deep learning for stroke risk prediction," IEEE J. Biomed. Health Inform., vol. 28, no. 3, pp. 1560–1571, 2024.

[15] A. Kumar and S. Verma, "Comparative analysis of CNN architectures for brain stroke detection," IEEE Access, vol. 11, pp. 89 214–89 226, 2023.

[16] F. Rahman et al., "Real-time stroke detection using lightweight deep learning models," IEEE Embedded Syst. Lett., vol. 16, no. 1, pp. 12–15, 2024.

[17] J. Morales and P. Ruiz, "Cloud-based AI systems for remote stroke diagnosis," IEEE Internet Comput., vol. 28, no. 1, pp. 44–52, 2024.

[18] N. Sharma and P. K. Singh, "Medical image enhancement techniques for stroke detection," IEEE Signal Process. Mag., vol. 41, no. 2, pp. 89–98, 2024.

[19] Z. Li et al., "Deep residual networks for brain abnormality detection," IEEE Trans. Neural Netw. Learn. Syst., vol. 35, no. 4, pp. 1789–1801, 2024.

[20] D. Evans and M. Brown, "Ethical considerations of AI-assisted stroke diagnosis," IEEE Technol. Soc. Mag., vol. 43, no. 1, pp. 33–41, 2024.

[21] P. Roy et al., "Automated CT-based stroke diagnosis using ensemble deep learning," IEEE Access, vol. 11, pp. 102 311–102 323, 2023.

[22] S. Ahmed and K. Hassan, "Performance evaluation of deep learning models for medical image classification," IEEE Access, vol. 12, pp. 66 145–66 158, 2024.

[23] J. Kim and H. Park, "Clinical decision support systems for stroke using AI," IEEE J. Transl. Eng. Health Med., vol. 12, pp. 1–9, 2024.

[24] V. Rao and S. Kulkarni, "Noise reduction and preprocessing strategies for brain CT images," IEEE Signal Process. Lett., vol. 31, pp. 450–454, 2024.

[25] M. Torres et al., "Deep learning-driven telemedicine solutions for stroke care," IEEE Access, vol. 12, pp. 73 510–73 522, 2024.

[26] L. Wang and X. Zhao, "Hybrid CNN models for stroke lesion detection," IEEE Trans. Med. Imaging, vol. 44, no. 1, pp. 115–126, 2025.

[27] S. Banerjee and R. Dutta, "Artificial intelligence in emergency stroke diagnosis," IEEE Pulse, vol. 16, no. 1, pp. 24–31, 2025.

[28] K. Matsumoto et al., "Explainable deep learning models for neuroimaging-based stroke prediction," IEEE J. Biomed. Health Inform., vol. 29, no. 2, pp. 980–991, 2025.

[29] A. El-Sayed and M. Ibrahim, "Scalable AI frameworks for large-scale medical image analysis," IEEE Cloud Comput., vol. 12, no. 1, pp. 60–69, 2025.

[30] R. Nair and S. Mohan, "Future directions of deep learning in stroke diagnosis and rehabilitation," IEEE Rev. Biomed. Eng., vol. 18, pp. 45–58, 2025.