

A REVIEW PAPER ON SEISMIC ANALYSIS OF OLD MASONRY BUILDINGS USING EQUIVALENT STATIC METHOD

Rashmi Sakalle¹, Nitin Tiwari², Saadiya Hamid Reshi³

^{1,2}Assistant Professor, Dept. of Civil Engineering, T.I.E.I.T, M.P, India

³M.Tech Scholar, Dept. of Civil Engineering, T.I.E.I.T, M.P, India, India

Abstract - In heritage protection, there is vital necessity to recognize the impending seismic risk in prevailing historic buildings for hazard moderation, disaster alertness and preceding knowledge of probable hazards. Seismic risk estimation remains centered on safety assessment, which necessitates qualitative and computable data. This data is necessary before making slightly intervention verdict. The qualitative data is visual inspection of degenerations, structural damages and depreciations; and the computable data requires laboratory tests, structural analysis etc. Obtaining the computable data is thorough method, which demands specialists and takes extra time and money. The fact that there are numerous historic buildings and a limited professional on this arena, it is very significant to create condition survey based on visual inspection as a first step of safety assessment technique. Conferring to the results inevitability of detailed examination and intercession and renovation works can ranked. This work aims to existing condition survey standards in general and laid emphasis on visual examination of the structure. The data given in this research is a visual examination method for judging the risk level of masonry monumental historic structures and then numerically analyzing the building by using equivalent static method and finally comparing the base shear, ensuring the safety of the structure from the damage due to seismic effects. The dissertation deals with Chaman Mahal, Bhopal (MP), as a case study.

Key Words: Equivalent static method, Seismic Analysis, Historic buildings, Visual assessment.

1. INTRODUCTION

This Masonry buildings are widely used for construction not only in India but in many other countries of the world. There are numerous advantages of masonry constructions over both types of construction i.e.; reinforced concrete and steel such as, thermal comfort, sound control, possibility of addition and alteration after construction, less formwork, easy and inexpensive repair, use of locally available materials, need of less skilled labour, less engineering intervention etc. However, there are some disadvantages as well, particularly, when it built in seismic environment. The seismic resistance capacity of masonry construction is relatively low in comparison to engineered constructions. Therefore, many developed nations have imposed certain restrictions on the use of unreinforced masonry constructions.

1.1 Background and Condition survey of chaman mahal

Chaman Mahal or the "Garden Palace" is an appropriate name for the marvellous palace built in 1715 by Dost Mohammad Khan, the Afghan commander who ruled Islam nagar of Bhopal, Madhya Pradesh, for a very short time. The sandstone palace is a remarkable sight. The palace has a Sheesh Mahal comprising of twelve doors that stands with pride at the entrance. The main attraction of the palace is a brilliant garden situated in the middle of the palace, having beautiful fountains for company. The palace is an example of a rich blend of Mughal and Malwa style of architecture. The columns and arches decorated with motifs of intricately designed flowers.

1.2 Brief overview on provisions of IS 1893: 2002

Earthquake motion causes vibration of the structure leading to inertia forces. Thus structure must be able to safely transmit the horizontal and the vertical inertia forces generated in the super structure through the foundation to the ground. Hence, for most of the ordinary structures, earthquake-resistant design requires ensuring that the structure has adequate lateral load carrying capacity. Seismic codes will guide a designer to safely design the structure for its intended purpose.

Seismic codes are unique to a particular region or country. In India, IS 1893 is the main code that provides outline for calculating seismic design force. This force depends on the mass and seismic coefficient of the structure and the latter in turn depends on properties like seismic zone in which structure lies, importance of the structure, its stiffness, the soil on which it rests, and its ductility. Part I of IS 1893:2002 (here after we refer it as the code) deals with assessment of seismic loads on various structures and buildings. Whole the code centres on the calculation of base shear and its distribution over height. Depending on the height of the structure and zone to which it belongs, type of analysis i.e., static analysis or dynamic analysis is performed.

In this dissertation, STATIC ANALYSIS performed for the building.

2. LITERATURE REVIEW

Irjet Meltem Vatan [1] the study aimed to provide condition survey criteria in general and laid emphasis on visual examination as a first stage of protection assessment. In heritage conservation, there is critical necessity to recognize

the potential seismic risk in current historic buildings for hazard mitigation, disaster preparedness and preceding awareness of potential risks. Seismic hazard assessment based on safety evaluation, which have need of qualitative and quantitative records. This record is essential before making any intervention conclusion. The qualitative data is visual examination of decays, structural damages and depreciations; and the quantitative data entails laboratory tests, structural analysis etc. Attaining the quantitative data is thorough process, which demands specialists and takes additional time and money. The fact that there are numerous historic structures and a few specialists on this field it is very significant to make condition survey based on visual inspection as a prior stage of safety evaluation method. According to these outcomes requirement of broad examination, intervention and renovation works can prioritized.

Neethu Gopal, Sankaranarayanan K.M et al. 2017 [2]: This paper focused on the analytical study of various masonry structures under numerous seismic conditions and the mitigation practices. It concluded the facts that Masonry structures belong to the most vulnerable class of structures, which have experienced substantial destruction or even complete demolition in earthquakes. Non-linear seismic analysis is beneficial for evaluating inelastic strength and deformation of the building. The strength capacity varies, depends on the masonry parameters

Sourabh Bhargava, Mr. V. S. Parihar, 2017 [3] studied on the Earthquake Resistant Low Cost Construction Methods. As in some parts of India, people live in villages and small houses having short income, thus more susceptible to earthquake effects thus additional loss of lives. There are many methods to resist earthquake but they are very expensive and not used by everyone. So they studied some useful low price methods to resist earthquake effects. The purpose of the research paper was how to save lives through use of low cost construction methods and proper seismic information.

Kamran, Shakeel Ahmad et al. 2016 [4] Studied seismic performance of a heritage brick masonry structure. For this context, nonlinear time history analysis done using SAP 2000 considering non-linearity of the material. Various mode shapes with their equivalent natural frequencies and stresses (normal and shear) attained. These stresses were equated with the permissible stresses provided in code of practice for unreinforced masonry structures (IS1905-1987).

Mahmud Sami Donduren 2016 [5] Horizontal earthquake forces affecting the masonry walls affect the walls in the negative direction. In this study, the performances and types of damages of masonry structures under the effect of earthquake defined. Moreover, the stresses in masonry structure elements calculated by considering the reactions of masonry structures in response to the effect of earthquakes. The structure modeled according to the particular earthquake region. The structure weight was determined

according to the stated slab, hatil (vertical or horizontal RC tie members), wall thicknesses, and the earthquake loads obtained in terms of equivalent earthquake load method. The stresses that took place in the walls against the loads were calculated and compared with allowable stress. The selected model structure was determined with FEDRA computer program. Stress distribution patterns were on the walls.

Zeljka Radovanovic, Radmila sindic et al. 2015 [6]: This paper proposes the research of the test results of mechanical properties of masonry walls. As part of the planned analysis, the main objective is to ascertain the compressive strength, elasticity modulus, shear modulus, and the characteristic stability on the tensile of the masonry walls. Experimentally resolved values for the modulus of elasticity of the tested walls are more than those provided in regulations PIOVS'91, EN 1996-1-1: 2005; ACI 530. Values of characteristic compressive strength attained analytically and based on equations that given in national and international standards are larger than the values of the characteristic compressive strengths of the walls that we have observed.

Narayanan S P, Sirajuddin M 2013 [7] Brick masonry unveils different directional properties due to the mortar joints, which act as planes of weakness, resulting in brick masonry structures viewing complex and non-linear mechanical behavior. The examination of mechanical behavior of brick masonry remains a true challenge. Properties of brick masonry components are significant in the FEM analysis of masonry structures. Three varieties of brick and three-mix proportion of mortar considered for experiments. Compressive strength, water absorption, Modulus of elasticity and Poisson ratio of bricks and Compressive strength, Modulus of elasticity, Poisson ratio and density of different mortars were resolute. The outcomes were concomitant and discussed and suitable values for non-linear FE analysis of masonry buildings suggested.

Mohammad Adil Dar, Prof (Dr) A.R. Dar, et al. 2013[8]: This paper aimed on the provisions that apart from the recent methods, which well acknowledged in the codes of practice. There are some other old traditional earthquake resistant methods, which have verified to be in effect for resisting earthquake loading and cost effective with easy constructability and various recommendations for earthquake resistant structures provided in it.

Michele Betti and Luciano Galano 2012[9]: The paper investigated the seismic susceptibility of a specific monumental masonry structure. The structural behavior of the Palace examined using a finite element model in which the non-linearity of the masonry considered by proper constitutive assumptions. The seismic behavior estimated by the pushover method, agreeing to the Italian Technical Recommendations. The outcomes compared with the ones acquired by a simplified approach based on the kinematic theorem of limit analysis. Assessments of the expected seismic demand vs the seismic capacity of the building

authorize the weakness of this type of structure to suffer wide destruction under earthquakes, as often perceived in similar building typologies. Moreover, the comprehension of the structural behavior under seismic loading consents the identification of an appropriate retrofitting strategy.

J. Snoj et al. 2012 [10] the seismic performance of prevailing masonry buildings were affected by diverse suspensions. The experimental setup based on the measurement of ambient and forced vibrations on an old two-storey masonry building. The vibration periods assessed and which based on two type of measurement, these are associated and seismic performance of the building evaluated for the near collapse limit state. A prevailing masonry building's seismic analysis is very challenging criteria. The chance to lessen the uncertainty in modeling is to measure ambient or forced vibrations. Time or frequency domain techniques based on the assessment of natural frequencies. The empirical assessment of natural frequencies based on the ambient vibrations and the forced vibrations. It estimates the vibration of building produced by trains. The Centre of the three corners of the roof storey contains 3D velocity sensor, which measures the vibrations. Then carried out the Fourier spectra analysis. In this experimental approach, the wider frequency ranges of the forced vibrations assessments the higher frequencies while allowing the small amount of time, the first natural frequency is not flawless. Here by using 3Muri program, developed a pseudo 3D non-linear structural model. The non-linear time history and pushover analysis is used. The building's uncertain modeling parameters have huge influence on the computed vibration period.

Nataliya Y. Vorontsova 2012 [11]: This paper studied about various means of providing seismic resistance to structures; on one side the traditional tactics to enhance the bearing capacity of structures, and on the other side – a technique to adapt or alter the dynamic performance of structures and to provide accessibility of the seismic isolation features and damping. In spite of the circumstance that there is an excessive amount of different proposals for renovation or strengthening structures, which might used in architectural monuments, not all of them have been applied at specific structures and verified by earthquake.

Pere Roca et al. 2005 [12] studied the strength capacity of masonry wall buildings. They used the equivalent frame method, which to be develop for capably simulating the service and ultimate response of structural system of masonry load bearing wall. The non-linear response noted by the use of biaxial equations. This process supports the prediction of whole response of the masonry constructions and their failure circumstances. It illustrates compatibility between wall panels and the transverse members joining them. The constitutive equations for the non-linear analysis of the masonry element have implemented for permitting the use of the method for the valuation for the ultimate capacity of masonry structure comprising the load bearing or shear wall.

K S Jagadish, S Raghunath, et al. 2003 [13] showed behavior of masonry constructions throughout earthquake. This paper attempted to assess the behavior of masonry constructions based on the category of masonry used in places like Bhuj, Anjar, Bhachau, Morbi, Samakhlyali and numerous other places. Several masonry constructions had used earthquake resistant features like lintel bands and corner reinforcements. The cracking and failure arrangements of such structures had observed. The paper concluded with a discussion on the relevance of the current codal provisions for earthquake resistance of masonry constructions and the direction of further investigation in the area.

Durgesh C. Rai 2000 [14] provided Upcoming developments in earthquake-resistant design of buildings. Earthquake-resistant design of buildings has developed into an exact multi-disciplinary arena of engineering wherein various stimulating progresses are yet to come. Most prominent among these are:

- (a) Inclusive probabilistic investigation and design approach.
- (b) performance-based design codes.
- (c) Multiple annual probability hazard maps for response spectral accelerations and peak ground accelerations with improved characterization of site soils, topography, near-field effects.
- (d) New structural systems and devices using non-traditional civil engineering resources and methods.
- (e) New refined analytical tools for reliable prediction of structural response, including nonlinearity, strength and stiffness degradation due to cyclic loads, geometry effects and more importantly, effects of soil structure interaction. Some substantial growths that the coming years will observe were also discussed in this paper.

Paulo b. Lourenço and Jan G. Rots 1997 [15] A lot of determination was being put into investigation on homogenization techniques for the examination of masonry buildings. The performance of the two step homogenization, which is based on the assumption of layered materials, was assessed in this paper by means of two examples. It was shown that large errors were likely to occur in the homogenization process if large differences of stiffness (>10) between the two masonry constituents were found. Therefore, the use of this technique in the presence of nonlinear material behavior called for great care.

3. CONCLUSIONS

Technology is accessible to considerably improve the earthquake associated disasters. This is confirmed by nominal destruction usually without any loss of life when moderate to severe earthquake strikes developed countries, however even a moderate earthquake cause's enormous destruction in developing countries as has been perceived in

recent earthquakes. The cause being that quake resistant methods rigorously followed in various countries where as such recommendations despondently violated in developing countries. The supervision system well organized and operative in developed countries, and it is not similar in developing countries – so the government should ensure the implementation of earthquake resistant design guiding principles. Thus, it is here that civil engineers in general and structural engineers in particular have a great role to play in modifying the anguishes, affected by earthquake related destructions. Hence different inferences based on the research are summarized below: -

1. The fact that there are numerous historic structures and a few specialists on this field it is very significant to make condition survey based on visual inspection as a prior stage of safety evaluation method.

2. Masonry structures belong to the most vulnerable class of structures, which have experienced substantial destruction or even complete demolition in earthquakes. Non-linear seismic analysis is beneficial for evaluating inelastic strength and deformation of the building.

3. Grade of mortar must be according to codes listed for diverse earthquake zones.

4. Horizontal bands must be provide at plinth, lintel and roof levels as per code.

5. The equivalent frame method, which is to be develop for capably simulating the service and ultimate response of structural system of masonry load bearing wall. The non-linear response noted by the use of biaxial equations. This process supports the prediction of whole response of the masonry constructions and their failure circumstances.

6. Masonry unveils different directional properties due to the mortar joints, which act as planes of weakness, resulting in brick masonry structures viewing complex and non-linear mechanical behavior.

REFERENCES

1. Meltem Vatan, "Condition Survey of Historic Buildings by Visual Inspection - Case Study: Murat Pasha Mosque", International Journal of Electronics, Mechanical and Mechatronics Engineering Vol.2 Num.1 Pp. (147-156).
2. Neethu Gopal, et al. (2017), "Behavior of Masonry Buildings Under Seismic Action" International Research Journal of Engineering and Technology (IRJET), e-ISSN: 2395 -0056, Volume: 04 Issue: 04, p-ISSN: 2395-0072.
3. Sourabh Bhargava, et al. (2017), "A Study on the Earthquake Resistant Low Cost Construction Techniques", International Journal for Research in Applied Science & Engineering Technology (IJRASET), Volume 5 Issue IV, April 2017 IC Value: 45.98 ISSN: 2321-9653.

4. Kamran, Shakeel Ahmad et al. (2016), "Seismic Performance of a heritage school building", 11th International symposium on Plasticity and impact mechanics, implast.
5. Mahmud Sami Donduren (2016), "Calculation of Loads and Stresses Acting on Masonry Walls, International Journal of Applied Mathematics, Electronics and Computers, ISSN: 2147-8228/2147.
6. Zeljka Radovanovic, et al. (2015) "The Mechanical Properties of Masonry Walls-Analysis of the Test Results, Procedia Engineering 117 (2015) 865 – 873.
7. Narayanan S P, Sirajuddin M (2013) "Properties of Brick Masonry for FE modeling", American Journal of Engineering Research (AJER) e-ISSN: 2320-0847 p-ISSN: 2320-0936 Volume-1 pp-06-11
8. Mohammad Adil Dar, et al. (2013), "A Study on Earthquake Resistant Construction Techniques" American Journal of Engineering Research (AJER) e-ISSN: 2320-0847 p-ISSN: 2320-0936 Volume-02, Issue-12, pp-258-264.
9. Michele Betti and Luciano Galano (2012), "Seismic Analysis of Historic Masonry Buildings: The Vicarious Palace in Pescia (Italy)" Buildings 2012, 2, 63-82; doi:10.3390/buildings2020063.
10. J.Snoj, M.Osterreicher and M.Dolsek (2012), "Experimentally supported modeling of an existing masonry building by measuring ambient and forced vibrations", Proceeding of 15th World Conference of Earthquake Engineering, LISBOA2012.
11. Nataliya Y. Vorontsova (2012), "Strengthening of Historical Monuments in Seismic Regions" 15 WCEE, LISBOA 2012.
12. Pere Roca et al. (2005), "Strength Capacity of Masonry Wall Structures by the Equivalent Frame Method", Journal of Structural Engineering, Vol. 131, pp 1601-1610.
13. K S Jagadish et al. (2003), "Behavior of masonry structures during the Bhuj earthquake of January 2001", Proc. Indian Acad. Sci. (Earth Planet. Sci.), 112, No. 3, September 2003, pp. 431-440.
14. Durgesh C. Rai (2000), "Future trends in earthquake-resistant design of structures", SEISMOLOGY 2000.
15. Paulo B. Lourenço and Jan G. Rots (1997), "on the use of homogenization techniques for the analysis of masonry structures", Masonry international, vol. 11, No. 1997.