

# Development, Design and Optimization of High Power Permanent Magnet DC Motor for Short Duration Applications

Pranav Ramnath Khamitkar<sup>1</sup>, Mehol Sanjay Abanavay<sup>2</sup>

<sup>1,2</sup>Department of mechanical engineering, Trinity College of engineering and research, Pune

\*\*\*

**Abstract** - An electric motor is an electrical machine that converts electrical energy into mechanical energy. Electric motors are used to produce linear or rotary force (torque). The reverse of this is the conversion of mechanical energy into electrical energy and is done by an electric generator, which has much in common with a motor. Motor is most widely used prime mover considering its size and input power requirements. In this paper we will discuss on design and optimization of PMDC motor for high power to weight ratio for short duty cycle. By lowering the net resistance of armature and maximizing the net magnetic flux density we can increase the power output of motor.

**Key Words:** High power motor, Generator, Motor, Neodymium, Motor Armature, EV's. Etc

## 1. INTRODUCTION

There are various types of prime mover used to drive various machines such as IC engines, turbines, motors etc. these are the mandatory parts required for functionality of any machine. . The largest of electric motors are used for ship propulsion, pipeline compression and pumped-storage applications with ratings reaching 100 megawatts. Electric motors may be classified by electric power source type, internal construction, application, type of motion output, and so on. Most electric motors operate through the interaction between an electric motor's magnetic field and winding currents to generate force. In certain applications, such as in regenerative braking with traction motors in the transportation industry, electric motors can also be used in reverse as generators to convert mechanical energy into electric power. A PMDC motor does not have a field winding on the stator; instead it has permanent magnets to provide the magnetic field against which the rotor field interacts to produce torque. Compensating windings in series with the armature may be used on large motors to improve commutation under load. Because this field is fixed, it cannot be adjusted for speed control. Permanent Magnetic fields (stators) are convenient in miniature motors to eliminate the power consumption of the field winding. Permanent Magnets could not be made to retain high flux if they were disassembled; field windings were more practical to obtain the needed amount of flux. However, large Permanent Magnets are costly, as well as dangerous and difficult to assemble. To minimize overall weight and size, miniature PM motors may use high energy magnets made with neodymium or other strategic elements; most such are neodymium-iron-boron alloy. With their

higher flux density, electric machines with high-energy Permanent Magnets are at least competitive with all optimally designed singly-fed synchronous and induction electric machines. Miniature motors resemble the structure in the illustration, except that they have at least three rotor poles (to ensure starting, regardless of rotor position) and their outer housing is a steel tube that magnetically links the exteriors of the curved field magnets. In upcoming days electrical motors are going to play an important role in the automobile industry. Due to continuous decreasing fossil fuels levels like petrol diesel and increasing their rates people have started liking electrical vehicle (EV'S) as an option. Companies like FIAT and TESLA have started developing electrical vehicles looking at its future scope. The main problem in front of electric vehicle is optimisation of batteries and motor. This paper can help understanding ways to optimise electrical PMDC motor for various applications.

## 2. PROBLEM STATEMENT

In this article we will optimize electrical properties by reducing net resistance of armature windings, by increasing number of poles and hence the net result will reflect as improvement in motor power output at same magnetic configuration. In this paper we designed a motor which has low weight up to 5kg having power output up to 8HP power. The Permanent motors use permanent magnets to generate magnetic flux. As the magnet has constant magnetic flux density (Neodymium: 1-1.4 W/m<sup>2</sup> Ferrite: 0.05W/m<sup>2</sup>) it is difficult to achieve more power output in PMDC motor. Hence it is necessary to improve electrical properties in order to improve the net power output.

## 3. OBJECTIVES

The objective of "Design, optimization and development of high power to weight ratio permanent magnet DC motor for short duration applications" are as follows:

- To decrease the size and total weight of the motor
- To increase the net power output by optimizing the electrical and magnetic design consideration
- To reduce the net thermal losses

#### 4. DESIGN of motor

- **Stator**

Mild steel cylinder is used to manufacturing stator as it has good magnetic permeability. The stator cylinder is designed more thick in order to dissipate heat energy generated during the working of the motor.

- **Magnets**

Neodymium magnets (NdFeB n35sh 175) are used due to their higher magnetic flux density. The magnets are stacked in four sets as the motor is four poles. Spacers are provided to fix the motors rigidly at their position.

- **Shaft**

The shaft of the motor is designed to withstand higher power and torque output. En-24 (AISI 4340) material is used for shaft, and it is hardened to 30 HRC.



Figure: Shaft used in motor

- **Brushes**

Copper Graphite brushes are used for maximum current conduction at minimum wear and tear.

- **Motor Armature**

The motor we designed is four pole parallel winding motor with skewed armature to reduce cogging effect.



Figure: Motor Armature

- **Commutator**

The armature wires are soldered to commutator in the motor. The soldering is done to withstand higher centrifugal force due to high RPM.

- **Designed layout of the motor**

First we design CAD model of motor on FUSION 360 Software as shown in figure below. This figure is exact replica of motor.



Figure: CAD model of motor

This model is exact replica of our final motor. Using this designed layout of the motor we manufactured the motor.

## 5. OPTIMISATION

We optimized the motor as follows -Soldered joints are replaced by welded joints to withstand against higher temperatures. The Initial specifications of motor resulted in high power and torque. But due to more current consumption the heat generated in motor was high which lead us to melting of soldered joints at commutator. Hence by further increasing net resistance of commutator winding we reduced current consumption.

## 6. RESULT AND TESTING

The final motor assembly weighs 4.8KG. The motor is designed for 48V DC at 6140 RPM. The variation in current consumption with respect to Voltage is given in observation table below

Sr. No.	Voltage input	Current Consumption at No load	Motor RPM	Stall Current
01	12	2 A	1625	118 A
02	24	4 A	3160	242 A
03	48	7 A	6140	450 A

Hence the Final Specifications achieved are as follows,

Motor Weight: 4.8 Kg

Working Voltage: 48V

Current Consumption: 7A (No Load)

Stall Torque: 45N-m

Rpm at 48V: 6140rpm



Weight of Working model of motor

## 7. CONCLUSIONS

In this motor we optimized electrical specifications which lead us to manufacturing of high power permanent magnet dc motor at minimum weight possible. As the power to weight ratio is high the duty cycle of the motor is less because thermal mass available for heat dissipation is not sufficient .external cooling can help to increase the duty cycle of the motor

## ACKNOWLEDGEMENT

We are profoundly grateful to our guide ADROIT SYSTEM and Mr.Shridhar Naidu for their expert and continuous encouragement with timely guidance, interest, and curiosity in work for the completion of this paper report.

## REFERENCES

- [1] "Design of Machine Element by V. B. Bhandari Third Edition 2015
- [2] "Electrical Machine Design" by A. K Sawhney Eighteenth Edition
- [3] "Power electronics and motor drives" by Bimal Bose First edition 2006
- [4] "Strength of Materials" by S. Ramamrutham and R. Narayanan Eighteenth edition 2016
- [5] Wikipedia