

STUDY ON HIGH STRENGTH CONCRETE WITH ADDITION OF FLY ASH AND HEMP FIBER

M. YESWANTH¹, C. KEERTHANA²

¹Assistant Professor, Department of Civil Engineering, Nandha Engineering College, Tamilnadu, India

²PG Student, Department of Civil Engineering, Nandha Engineering College, Tamilnadu, India

Abstract - Hemp (*Cannabis sativa*) is one of the most available and widely produced bast fibers with high cellulose content. Interest in these fibers is warranted due to environmental protection challenges as well as their inherent properties such as low density, high specific strength, and stiffness. In addition, advanced research and progress have gone into increasing their mechanical performance through surface treatments and in the development of new materials. The most promising application for hemp fibers is as reinforcement in polymeric composites or through hybridization. Nonetheless, more research is needed to improve their properties and expand their range of applications. The biodegradability issue is one problem that must be addressed when considering long life-cycle applications as the reproducibility of these composites' final properties. This review is a comprehensive literature review on hemp fibers. It includes hemp fibers chemical and mechanical properties, surface modifications, hybrid composites, as well as current and future applications. The focus on High Performance concrete (HPC) has immensely increased due to utilization of large quantity of concrete, thereby leading to the development of infrastructure Viz., Buildings, Industrial Structures, Hydraulic Structures, Bridges and Highways etc. This paper includes the detailed study on the recent developments in High Performance Concrete, stressing more on the earthquake prone areas. It highlights the advantages and importance of High Performance concrete over conventional concrete. In this process adding fly ash and hemp fiber in addition to the High Strength Concrete. According to this the addition of fly ash and hemp fiber varies. The constant adding percentage of fly ash is 15% and hemp fiber varies like 0.05, 0.1, 0.15

Key Words: Hemp fiber, Bast fiber, Fly ash, High Strength Concrete (HPC), etc.,

1. INTRODUCTION

1.1 General

Concrete is a mixture of cement, fine aggregate and coarse aggregate, which is mainly derived from natural resources. Increasing population, expanding urbanization, climbing way of life due to technological innovations has demanded a huge amount of natural resources in the construction industry, which has resulted in scarcity of resources. This scarcity motivates the researchers to use, solid wastes generated by industrial, mining, domestic and

agricultural activities. They also studied the relationship between the concrete made using this type of materials; environmentally friendly concrete and green building rating systems. Issues like emission of carbon dioxide, use of energy, water, aggregates, fillers and demolition waste in concrete look less compatible with environmental requirement of a modern sustainable construction industry. At the same time, concrete made using agricultural wastes has shown better mechanical and durability properties in research which can result in sustainability points in the energy.

1.2 OBJECTIVES

The main objective of this study is to determine the suitable percentage of Fly ash and Hemp fiber in addition to the mixes and also to compare the results of two mixes.

1.3 SCOPE

To determine the properties of the materials. To examine the mechanical properties of hardened concrete. To determine the permeability range.

2. CONCRETE

2.1 LITERATURE REVIEW

The model data is based on a previous experimental study encapsulating natural industrial hemp fibers in plain concrete mixes, where twelve mixes were considered including one without fibers (control mix), one with polypropylene fibers, and ten with industrial hemp fibers [10]. Various physical and mechanical properties of hemp fibres were evaluated to assess their suitability for use as reinforcement in composite materials [6]. The focus on High Performance concrete (HPC) has immensely increased due to utilization of large quantity of concrete, thereby leading to the development of infrastructure Viz., [8]. Study on the use of natural hemp fibers as a composite in concrete mixes to improve performance of construction components and reduce depletion in natural resources [3]. One method of increasing the mechanical properties of natural fiber composites is by hybridizing them with another synthetic or natural fiber of superior mechanical properties [4].

2.2 PROPERTIES OF HIGH STRENGTH CONCRETE

The properties of high strength concrete are significantly different from those of normal strength concrete. These properties are examined in this section when the concrete is setting and hardening as well as in the hardened state. These properties should be taken into account while designing structures using high-strength concrete.

2.3 ADVANTAGE OF HIGH STRENGTH CONCRETE

The main advantages of high strength concrete are the following: Reduction in member size, resulting in an increasing in the usable floor space, a reduction in the quality of concrete, and a consequent reduction in construction time. Reduction on self-weight and a consequent reduction in the foundation in the foundation cost. Reduction in the area of the formwork and the time required for stripping forms. The ability to withstand large column loads with reasonable sizes of columns. Provision of large spans or elimination of a few columns or smaller beams for comparable spans, leading to a reduction in the story height from headroom considerations. Reduction in axial shortening effects in columns. Reduction in floor thickness and beam height. Elimination of a few footing because of adoption of larger spans. Superior durability and long-term performance. Lower creep and shrinkage. Larger stiffness as a result of a larger value of young's modulus of concrete. Reduced maintenance costs.

2.4 APPLICATION OF HIGH STRENGTH CONCRETE:

In the context of tall buildings and large-span bridges, it is clear that use of high-strength concrete leads to reduced column sizes and beam depths, in addition, it results in improved performance in terms of creep, shrinkages, and other elastic properties that yield a more favorable deformation pattern for tall buildings. The improved elastic properties also limit the sway and reduce elastic shortening and other secondary's effects. Hence high strength concrete has found applications of various structures use.

3. MATERIALS TO BE USED

3.1 CEMENT

Cement is a binder, a substance used for construction that sets, hardens, and adheres to other materials to bind them together. Cement is seldom used on its own, but rather to bind sand and gravel (aggregate) together. Cement mixed with fine aggregate produces mortar for masonry, or with sand and gravel, produces concrete. Concrete is the most widely used material in existence and is only behind water as the planet's most-consumed resource.

3.2 M-SAND

Manufactured is an alternative for river sand. Due to fast growing construction industry, the demand for sand has increased tremendously, causing deficiency of river sand in most part of the world. Due to depletion of good quality river sand for the use of construction, the use of manufactured sand has been increased. Another reason for use of M Sand is its availability and transportation cost.

3.3 COARSE AGGREGATE

Coarse aggregate is mined from rock quarries or dredged from river beds, therefore the size, shape, hardness, texture and many other properties can vary greatly based on location. Even materials coming from the same quarry or pit and type of stone can vary greatly. Most generally, coarse aggregate can be characterized as either smooth or rounded (such as river gravel) or angular (such as crushed stone).

3.4 FLY ASH

Fly ash is a fine powder that is a by product of burning pulverized coal in electric generation power plants. Fly ash is a pozzolan, a substance containing aluminous and siliceous material that forms cement in the presence of water. When mixed with lime and water, fly ash forms a compound similar to Portland cement.

3.5 HEMP FIBER

Hemp is a bast fiber plant similar to Flax, Kenaf, Jute, and Ramie. Long slender primary fiber on the outer portion of the stalk characterized bast fiber plants. It was probably used first in Asia. *Hemp* is also one of the bast fiber known to ancient Asians, long before the birth of Christ. The outer material contains the prized bast fibers and the inner is the hard, which is made up of short fibers. There are three main stages of producing fiber from industrial hemp – harvesting, retting and separation. Hemp is a sustainable and environmental friendly crop that can provide valuable raw materials to a large number of industrial applications. Traditionally harvested at full flowering for textile destinations, nowadays hemp is mainly harvested at seed maturity for dual-purpose applications and has a great potential as multipurpose crop. However, the European hemp fiber market is stagnating if compared to the growing market of hemp seeds and phytocannabinoids.

Hemp fibers have been used for centuries to manufacture clothes, bags, shoes, paper, building materials and insulation purposes.

Hemp fiber is also used as a food and is not the same as cannabinoids used for intoxication purposes. Hemp is cheaper than wood and it is a better material to be used for insulation purposes. Wood or timber is costly. These days it is not advisable to cut down trees keeping in mind the huge

loss it causes to our environment and biodiversity. Matrix options are limited due to lower processing temperatures. Poor matrix-fiber interfacial adhesion. Flammable, sensitive to UV, microbial, and fungus attack.

4. TESTS TO BE CONDUCTED

Fresh concrete tests such as Slump cone test, L-Box test, V-Funnel test are to be performed. Compressive strength test, Split tensile test and Flexural strength test are also proposed to be conducted. Mix designs are arrived by using IS 10262-2019

5. CONCLUSIONS

From the above journals it is evident that High Strength Concrete plays a vital role in construction industry. In addition to that the Fly ash and Hemp fiber are added and works been done

REFERENCES

1. Study of the durability of concrete reinforced with hemp fibers exposed to external sulfatic attack, Sami Ziane, Mohammed-Rissel Khelifa, Samy Mezhoud., Ph.D.
2. Industrial hemp fibers: an overview Joao P. Manaia , Ana T. Manaia And Lucia Rodrigues
3. Studies on Fiber-Reinforced Concrete using Industrial Hemp Fibers Elie Awwad, Mounir Mabsout, Bilal Hamad, Mohamad Talal Farran, and Helmi Khatib
4. Hemp fiber and its composites - A review Asim Shahzad
5. Optimizing Hemp Fiber Production for High Performance Composite Applications Salvatore Musio, Jörg Müssig, and Stefano Amaducci
6. A Study in Physical and Mechanical Properties of Hemp Fibres - Asim Shahzad
7. Properties of hemp fibre reinforced concrete composites., Zhijian Li, Xungai Wang, Lijing Wang
8. Study Of High Performance Concrete - Swati Choudhary, Rishab Bajaj, Rajesh Kumar Sharma
9. Study of High Strength Fibre Reinforced Concrete by using Two Types of Fibres Prof. Rahul D. Pandit, Dr .Abhijeet P. Wadekar
10. An Analytical Linear Model for Hemp-Reinforced Concrete - Elie Awwad, Mounir Mabsout, and Bilal Hamad, and Ghassan Chehab

11. Comprehensive Study of High Strength Concrete with and without Natural Organic Fibres - Rustam Sahu & Abhishek Tiwari